



Navigation



Extrusion 1-0-Wiki Pages

- [Main Page](#)
- [Best Papers](#)
- [Book Reviews](#)
- [Consultants Corner](#)
- [Extruder Software](#)
- [Extrusion Hints](#)
- [Safety](#)
- [Shop Tools](#)
- [Sponsors](#)
- [Technical Articles](#)

Search the Wiki

 >>

Viewing/Creating

- [Random Page](#)
- [Create a new Page](#)
- [All Pages](#)
- [Categories](#)

Account Management

- [Login/Logout](#)
- [Language Selection](#)
- [Your Profile](#)
- [Create Account](#)

Administration

- [Administration](#)
- [File Management](#)

Brought to you by:

The SPE Extrusion Division Board of Directors



Bevel Outside

Modified on Sunday, 01 February 2015 05:19 PM by [mpieler](#) Categorized as [Extrusion Hints](#)

[\(10\)](#) » [Twin Screw Changes](#) » [Underwater Pelletizer](#) » **Bevel Outside**

Bevel Outside
Vol. 18 #2, July 1991

Slitter blades, on a sheet line - Edge cut can be improved by sharpening blades with the bevel to the outside so that rough cut is allowed on the edge trim, but not on the sheet edge.

See also:

- [Roll edge quality](#)

Return to [Extrusion Hints](#)

Some of the icons were created by [FamFamFam](#)