



Navigation



Extrusion 1-0-Wiki Pages

- [Main Page](#)
- [Best Papers](#)
- [Book Reviews](#)
- [Consultants Corner](#)
- [Extruder Software](#)
- [Extrusion Hints](#)
- [Safety](#)
- [Shop Tools](#)
- [Sponsors](#)
- [Technical Articles](#)

Search the Wiki

  »

Viewing/Creating

- [Random Page](#)
- [Create a new Page](#)
- [All Pages](#)
- [Categories](#)

Account Management

- [Login/Logout](#)
- [Language Selection](#)
- [Your Profile](#)
- [Create Account](#)

Administration


- [Administration](#)
- [File Management](#)

Brought to you by:

The SPE Extrusion Division Board of Directors



Feed Throat Temperature

Modified on Sunday, 01 February 2015 05:31 PM by [mpieler](#) Categorized as [Extrusion Hints](#) 

[\(10\)](#) » [Time Dimension](#) » [High-Low Melt Blends](#) » [Feed Throat Temperature](#)


Feed Throat Temperature
Vol. 19, #2, June 1992

In single screw extrusion, the feed throat of the extruder should be approximately 110 120 degrees F, or "warm to the touch", to help in insuring that a stable feed is developed.

See also:

- [Feed throat configuration](#)
- [Feed throat cooling](#)
- [Feed throats](#)
- [Lower feed zone temperature](#)

[Return to Extrusion Hints](#)

Some of the icons were created by [FamFamFam](#) .