



Navigation



Extrusion 1-0-Wiki Pages

- [Main Page](#)
- [Best Papers](#)
- [Book Reviews](#)
- [Consultants Corner](#)
- [Extruder Software](#)
- [Extrusion Hints](#)
- [Safety](#)
- [Shop Tools](#)
- [Sponsors](#)
- [Technical Articles](#)

Search the Wiki

Viewing/Creating

- [Random Page](#)
- [Create a new Page](#)
- [All Pages](#)
- [Categories](#)

Account Management

- [Login/Logout](#)
- [Language Selection](#)
- [Your Profile](#)
- [Create Account](#)

Administration

- [Administration](#)
- [File Management](#)

Brought to you by:

The SPE Extrusion Division Board of Directors



Simulations

Modified on Sunday, 01 February 2015 10:09 PM by [mpieler](#) Categorized as [Extrusion Hints](#) (10) » [Hopper Segregation](#) » [Segmented Screws](#) » **Simulations**

Simulations
Vol.20 #3, Dec. 1993

In the numerical simulation of an extrusion process, it is essential to use the physical data that is as accurate as possible before one can evaluate the usefulness of the program.

See also:

- [Computer simulations](#)
- [Data collection 1](#)
- [Extrusion trials](#)

[Return to Extrusion Hints](#)

Some of the icons were created by [FamFamFam](#)