



## Navigation



## Extrusion 1-0-Wiki Pages

- [Main Page](#)
- [Best Papers](#)
- [Book Reviews](#)
- [Consultants Corner](#)
- [Extruder Software](#)
- [Extrusion Hints](#)
- [Safety](#)
- [Shop Tools](#)
- [Sponsors](#)
- [Technical Articles](#)

## Search the Wiki

  [»](#)

## Viewing/Creating

- [Random Page](#)
- [Create a new Page](#)
- [All Pages](#)
- [Categories](#)

## Account Management

- [Login/Logout](#)
- [Language Selection](#)
- [Your Profile](#)
- [Create Account](#)

## Administration

- [Administration](#)
- [File Management](#)

## Brought to you by:

The SPE Extrusion Division  
Board of Directors



# Early Detection

Modified on Sunday, 01 February 2015 10:12 PM by [mpieler](#) Categorized as [Extrusion Hints](#) 

[\(10\)](#) » [Cold Gearbox Oil](#) » [Overfilled Gearbox](#) » **Early Detection**

Early Detection  
Vol.20 #3, Dec. 1993


Check the screws and barrels periodically for corrosion and wear.

Early detection may indicate corrective actions to minimize major problems in the future.

See also:

- [Protect the barrel](#)
- [Screw wear](#)
- [Worn barrel](#)
- [Worn screw](#)

Return to [Extrusion Hints](#)

Some of the icons were created by [FamFamFam](#) .