



Navigation



Extrusion 1-0-Wiki Pages

- [Main Page](#)
- [Best Papers](#)
- [Book Reviews](#)
- [Consultants Corner](#)
- [Extruder Software](#)
- [Extrusion Hints](#)
- [Safety](#)
- [Shop Tools](#)
- [Sponsors](#)
- [Technical Articles](#)

Search the Wiki

  »

Viewing/Creating

- [Random Page](#)
- [Create a new Page](#)
- [All Pages](#)
- [Categories](#)

Account Management

- [Login/Logout](#)
- [Language Selection](#)
- [Your Profile](#)
- [Create Account](#)

Administration


- [Administration](#)
- [File Management](#)

Brought to you by:

The SPE Extrusion Division
Board of Directors



Hopper Magnets

Modified on Sunday, 01 February 2015 10:34 PM by [mpieler](#) Categorized as [Extrusion Hints](#) 
(10) » [Barrel Thermocouple Maintenance](#) » [Storage of Extruders](#) » [Hopper Magnets](#)

Hopper Magnets
Vol.21 #2, Oct. 1994


It is common practice to install magnets above the extruder feed throat to remove tramp metal from the pellet feed stream, but reground film scrap will not flow through conventional magnets.

There are special magnets available that can be installed in the fluff supply pipe if it is desirable to protect the extruder from tramp metal in the fluff.

See also:

- [Feed throats](#)
- [Hoppers](#)
- [Hopper segregation](#)

Return to [Extrusion Hints](#)

Some of the icons were created by [FamFamFam](#) .