



Navigation



Extrusion 1-0-Wiki Pages

- [Main Page](#)
- [Best Papers](#)
- [Book Reviews](#)
- [Consultants Corner](#)
- [Extruder Software](#)
- [Extrusion Hints](#)
- [Safety](#)
- [Shop Tools](#)
- [Sponsors](#)
- [Technical Articles](#)

Search the Wiki

 »

Viewing/Creating

- [Random Page](#)
- [Create a new Page](#)
- [All Pages](#)
- [Categories](#)

Account Management

- [Login/Logout](#)
- [Language Selection](#)
- [Your Profile](#)
- [Create Account](#)

Administration

- [Administration](#)
- [File Management](#)

Brought to you by:

The SPE Extrusion Division Board of Directors



Drive Speed Controller

Modified on Sunday, 01 February 2015 10:44 PM by [mpieler](#) Categorized as [Extrusion Hints](#) (10) » [Hose Clamp Safety](#) » [Preventative Maintenance List](#) » [Drive Speed Controller](#)

Drive speed controller
Vol. 21 #3, Dec. 1994

A fluctuating or incorrect RPM can lead to poor product quality or a change in output.

See also:

- [Decreased motor amps](#)
- [High motor amps](#)
- [RPM meters](#)

[Return to Extrusion Hints](#)

Some of the icons were created by [FamFamFam](#)