



## Navigation



## Extrusion 1-0-Wiki Pages

- [Main Page](#)
- [Best Papers](#)
- [Book Reviews](#)
- [Consultants Corner](#)
- [Extruder Software](#)
- [Extrusion Hints](#)
- [Safety](#)
- [Shop Tools](#)
- [Sponsors](#)
- [Technical Articles](#)

## Search the Wiki

  »

## Viewing/Creating

- [Random Page](#)
- [Create a new Page](#)
- [All Pages](#)
- [Categories](#)

## Account Management

- [Login/Logout](#)
- [Language Selection](#)
- [Your Profile](#)
- [Create Account](#)

## Administration


- [Administration](#)
- [File Management](#)

## Brought to you by:

The SPE Extrusion Division  
Board of Directors



# Data Collection 1

Modified on Sunday, 01 February 2015 11:05 PM by [mpieler](#) Categorized as [Extrusion Hints](#) 

[\(10\)](#) » [Sponsors](#) » [Technical Articles](#) » **Data Collection 1**

Data Collection 1  
Vol. 22 #2, Sept. 1995


During data entry on a modern data control system, the operator can lose sight of vital extruder parameters, e.g. melt pressure, motor load, and melt temperature, because the changes are made on different pages.

By providing separate display instruments for these values, the extrusion process can be checked quickly without scrolling through several pages on DCS screens.

## See also:

- [Calibrate tachs](#)
- [Color feeder calibration](#)
- [Computer simulations](#)
- [Control systems](#)
- [Document/document/document](#)
- [Extruder log book](#)
- [Extrusion data sheets](#)
- [Extrusion trials](#)
- [Melt pressure](#)
- [Patience](#)
- [Plot extruder performance](#)
- [Simulations](#)

Return to [Extrusion Hints](#)

Some of the icons were created by [FamFamFam](#) .