



Navigation



Extrusion 1-0-Wiki Pages

- [Main Page](#)
- [Best Papers](#)
- [Book Reviews](#)
- [Consultants Corner](#)
- [Extruder Software](#)
- [Extrusion Hints](#)
- [Safety](#)
- [Shop Tools](#)
- [Sponsors](#)
- [Technical Articles](#)

Search the Wiki

Viewing/Creating

- [Random Page](#)
- [Create a new Page](#)
- [All Pages](#)
- [Categories](#)

Account Management

- [Login/Logout](#)
- [Language Selection](#)
- [Your Profile](#)
- [Create Account](#)

Administration

- [Administration](#)
- [File Management](#)

Brought to you by:

The SPE Extrusion Division Board of Directors



Static Electricity Build Up

Modified on Sunday, 01 February 2015 11:23 PM by [mpieler](#) Categorized as [Extrusion Hints](#)

[\(10\)](#) » [Motor Overheating](#) » [Pressure Blips](#) » **Static Electricity Build Up**

Static electricity build up
Vol. 23 #1, May 1996

Anti Static Tinsel is useful in reducing static electricity build up in film rolls or moving webs. The 100% copper tinsel should be well grounded and allowed to lightly touch the full width of the moving web within a foot or two of where the operator could come in contact with the sheet or roll.

One source is TAKK Industries, Inc. (513) 353 4306.

See also:

- [Flex tube safety](#)
- [Reduce static in polymer processing operations](#)
- [Static eliminator](#)

[Return to Extrusion Hints](#)

Some of the icons were created by [FamFamFam](#)