



## Navigation



## Extrusion 1-0-Wiki Pages

- [Main Page](#)
- [Best Papers](#)
- [Book Reviews](#)
- [Consultants Corner](#)
- [Extruder Software](#)
- [Extrusion Hints](#)
- [Safety](#)
- [Shop Tools](#)
- [Sponsors](#)
- [Technical Articles](#)

## Search the Wiki

  »

## Viewing/Creating

- [Random Page](#)
- [Create a new Page](#)
- [All Pages](#)
- [Categories](#)

## Account Management

- [Login/Logout](#)
- [Language Selection](#)
- [Your Profile](#)
- [Create Account](#)

## Administration


- [Administration](#)
- [File Management](#)

## Brought to you by:

The SPE Extrusion Division  
Board of Directors



# Thermocouples

Modified on Monday, 02 February 2015 12:33 PM by [mpieler](#) Categorized as [Extrusion Hints](#)   
(10) » [Remove Buildup](#) » [Stainless Steel Components](#) » **Thermocouples**

Thermocouples  
Vol. 25 #2, Sept. 1998

Every maintenance department should have at least 1 variable depth melt probe (thermocouple) that can be used for troubleshooting or commissioning new equipment.


Once the true melt temperature and proper process conditions have been determined, the VDMP can be replaced with a less expensive, standard thermocouple for daily operation.

- John Perdikoulis, Compuplast Canada

See also:

- [Barrel zone override](#)
- [No service call](#)
- [Temperature controller calibration](#)
- [Thermocouple connections 2](#)
- [Thermocouple wires](#)

Return to [Extrusion Hints](#)

Some of the icons were created by [FamFamFam](#) .