



Navigation



Extrusion 1-0-Wiki Pages

- [Main Page](#)
- [Best Papers](#)
- [Book Reviews](#)
- [Consultants Corner](#)
- [Extruder Software](#)
- [Extrusion Hints](#)
- [Safety](#)
- [Shop Tools](#)
- [Sponsors](#)
- [Technical Articles](#)

Search the Wiki

  »

Viewing/Creating

- [Random Page](#)
- [Create a new Page](#)
- [All Pages](#)
- [Categories](#)

Account Management

- [Login/Logout](#)
- [Language Selection](#)
- [Your Profile](#)
- [Create Account](#)

Administration


- [Administration](#)
- [File Management](#)

Brought to you by:

The SPE Extrusion Division
Board of Directors



Breaker Plate Maintenance

Modified on Monday, 02 February 2015 12:52 PM by [mpieler](#) Categorized as [Extrusion Hints](#) 
(10) » [Extrusion Pump Life](#) » [Maximum Channel Depth for High Rate](#) » **Breaker Plate Maintenance**

Breaker Plate Maintenance
Vol. 26 #1, March 1999


Breaker plates should be inspected for damage regularly. Breaker plates are often misused and abused. They are easily dropped and the edges can be bent causing alignment problems. Sometimes operators will use a hammer to drive the breaker plate out of the holder. This canpeen over the holes causing a dead spot and poor flow conditions. When this occurs, one needs to ream out the holes to restore proper flow path. A reamer will provide a smoother inside surface versus the rough surface of a drilled hole.

- John Wagner Jr., Mobil Chemical Co.

See also:

- [Breaker plate recess ring](#)
- [Breaker plates](#)
- [Clean breakers](#)

Return to [Extrusion Hints](#)

Some of the icons were created by [FamFamFam](#) .